

Ballance Agri-Nutrients

Chemwatch: 5374-54 Version No: 3.1

Version No: **3.1** Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	PastureSure Impact (NI)
Chemical Name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Fertiliser.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Ilance Agri-Nutrients	
Address	161 Hewletts Rd Mount Maunganui New Zealand	
Telephone	+64 800 222 090	
Fax	Not Available	
Website	www.ballance.co.nz	
Email	customerservices-mount@ballance.co.nz	

Emergency telephone number

Association / Organisation	CHEMCALL	
Emergency telephone numbers	Freephone: 0800 CHEMCALL (0800 243 622) (24 Hours/ 7 Days)	
Other emergency telephone numbers	Not Available	

SECTION 2 Hazards identification

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

ChemWatch Hazard Ratings

	Min Max	_ 1
Flammability	1	1
Toxicity	2	0 = Minimum
Body Contact	2	1 = Low
Reactivity	1	2 = Moderate
Chronic	0	3 = High 4 = Extreme

Classification ^[1] Acute Toxicity (Oral) Category 4, Serious Eye Damage/Eye Irritation Category 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.1D (oral), 6.4A

Chemwatch Hazard Alert Code: 2

Issue Date: **15/09/2022** Print Date: **18/09/2022** L.GHS.NZL.EN.E

Hazard pictogram(s)	
Signal word	Warning

Hazard statement(s)

H302	Harmful if swallowed.
H319	Causes serious eye irritation.

Precautionary statement(s) Prevention

P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves, protective clothing, eye protection and face protection.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	f eye irritation persists: Get medical advice/attention.	
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.	
P330	Rinse mouth.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7778-18-9	30-60	calcium sulfate
57-13-6	10-30	urea
7757-93-9	10-30	calcium phosphate, dibasic
7758-23-8	1-10	calcium phosphate, monobasic
57-55-6	<1	propylene glycol
Not Available	10-30	Ingredients determined not to be hazardous
Legend:	 Classified by Chemwatch; 2. Classification drawn from C&L 	assification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; * EU IOELVs available

SECTION 4 First aid measures

Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicate by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.

otherwise:

INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 NOTE: Wear a protective glove when inducing vomiting by mechanical means.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility + Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location.
Fire/Explosion Hazard	 Solid which exhibits difficult combustion or is difficult to ignite. Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited; once initiated larger particles up to 1400 microns diameter will contribute to the propagation of an explosion. A dust explosion may release large quantities of gaseous products; this in turn creates a subsequent pressure rise of explosive force capable of damaging plant and buildings and injuring people. Usually the initial or primary explosion takes place in a confined space such as plant or machinery, and can be of sufficient force to damage or rupture the plant. If the shock wave from the primary explosion enters the surrounding area, it will disturb any settled dust layers, forming a second dust cloud, and often initiate a much larger secondary explosion. Combustion products include: carbon monoxide (CO) carbon moxides (NOX) phosphorus oxides (POX) sulfur oxides (SOX) metal oxides other pyrolysis products typical of burning organic material. In fire situation urea melts and flows, on further heating it decomposes giving off ammonia gas. Thermal and oxidative degradation products can include ammonia, biuret, and cyanuric acid,. May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Use dry clean up procedures and avoid generating dust. Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing. Prevent, by any means available, spillage from entering drains or water courses. Recover product wherever possible.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions) Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. Establish good housekeeping practices. Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Calcium sulfate: reacts violently with reducing agents, acrolein, alcohols, chlorine trifluoride, diazomethane, ethers, fluorine, hydrazine, hydrazinium perchlorate, hydrogen peroxide, finely divided aluminium or magnesium, peroxyfuroic acid, red phosphorus, sodium acetylide sensitises most organic azides which are unstable shock- and heat- sensitive explosives may form explosive materials with 1,3-di(5-tetrazoly)/triazene is incompatible with glycidol, isopropyl chlorocarbonate, nitrosyl perchlorate, sodium borohydride is hygroscopic; reacts with water to form gypsum and Plaster of Paris Utrea: forms anhydrous ammonia and nitrous vapours on contact with hot surfaces reacts violently with strong oxidisers, chlorine, inorganic chlorides, chlorides, chloride, dichromates, dicyanofurazan, fluorine, gallium perchlorate, hydrogen peroxide, lead dioxide, nitrates, nitrites, permanganates, perchlorate, thanium tetrachloride, triethylenetetramine ignites or explodes on reaction with ammonium nitrate, chromyl chloride, nitrosyl perchlorate, phosphorus pentachloride may form highly explosive nitrogen trichloride on contact with hexanitroethane, perchlorate, phosphorus pentachloride may form highly explosive nitrogen trichloride on contact with hexanitroethane, perchloryl fluoride, sodium perchlorate, trichloroisocyanuric acid, hypochlorites and other chlorinating agents is incompatible with oxalic acid, sodium dichlorocyanurate Phosphates are incompatible to formation of highly toxic and flammable phosphine gas in the presence of strong reducing agents such as hydrides. Partial oxidation of phosphates by oxidizing agents may result in the release of toxic phosphorus oxides.

X — Must not be stored together

х

0 — May be stored together with specific preventions

+ - May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	calcium sulfate	Calcium sulphate (Gypsum, Plaster of Paris)	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	propylene glycol	Propane-1,2-diol, Vapour and particulates	150 ppm / 474 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	propylene glycol	Propane-1,2-diol, Particulates only	10 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
urea	30 mg/m3	280 mg/m3		1,700 mg/m3
propylene glycol	30 mg/m3	1,300 mg/m3		7,900 mg/m3
Ingredient	Original IDLH		Revised IDLH	
calcium sulfate	Not Available		Not Available	
urea	Not Available		Not Available	

Notes:

Page 5 of 11 PastureSure Impact (NI)

Ingredient	Original IDLH	Revised IDLH
calcium phosphate, dibasic	Not Available	Not Available
calcium phosphate, monobasic	Not Available	Not Available
propylene glycol	Not Available	Not Available
Occupational Exposure Banding		
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
	·····	Cocupational Exposure Bana Ennit
urea	E	≤ 0.01 mg/m ³
urea calcium phosphate, dibasic		· ·

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.
See Hand protection below
The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.
See Other protection below
 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

PastureSure Impact (NI)

Material	СРІ
PE/EVAL/PE	А
BUTYL	С
NATURAL RUBBER	С
PVA	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AK-AUS P2	-	AK-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AK-AUS / Class 1 P2	-
up to 100 x ES	-	AK-2 P2	AK-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO =

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

 The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

 Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

 Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

· Use approved positive flow mask if significant quantities of dust becomes airborne.

Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance Coloured particles; partly soluble in water.			
Appearance	Coloured particles, party soluble in water.		
Physical state	Divided Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.	
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.	

PastureSure Impact (NI)	stureSure Impact (N	II)
-------------------------	---------------------	-----

Skin Contact	 The material may produce mild skin irritation; limited evidence or practical experience suggests, that the material either: produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (non allergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of interacellular ostare strated or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. 		
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.		
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. A prime symptom is breathlessness. Lung shadows show on X-ray.		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
PastureSure Impact (NI)	Not Available	Not Available	
		IRRITATION	
calcium sulfate	Inhalation(Rat) LC50; >3.26 mg/l4h ^[1]	Not Available	
	Oral (Rat) LD50; >1581 mg/kg ^[1]		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	dermal (rat) LD50: 8200 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]	
urea	Oral (Rat) LD50; 8471 mg/kg ^[2]	Skin (human): 22 mg/3 d (I)- mild	
		Skin: no adverse effect observed (not irritating) ^[1]	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: >7940 mg/kg ^[2]	Eye (rabbit): 8 on a scale of 110	
calcium nhosnhata, dihasic	Inhalation(Rat) LC50; >2.6 mg/l4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	
calcium phosphate, dibasic	Oral (Rat) LD50; >10000 mg/kg ^[2]	Skin (rabbit): 0 on a scale of 8	
		Skin: no adverse effect observed (not irritating) ^[1]	
		· · ·	
	TOXICITY	IRRITATION	
calcium phosphate, monobasic	Dermal (rabbit) LD50: >7940 mg/kg ^[2]	Eye : Severe	
monopasic	Inhalation(Rat) LC50; >2.6 mg/l4h ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]	
	Oral (Rat) LD50; 7100 mg/kg ^[2]	Skin: no adverse effect observed (not irritating) ^[1]	
	ΤΟΧΙCITY	IRRITATION	
	Dermal (rabbit) LD50: 11890 mg/kg ^[2]	Eye (rabbit): 100 mg - mild	
	Inhalation(Rat) LC50; >44.9 mg/L4h ^[2]	Eye (rabbit): 500 mg/24h - mild	
propylene glycol	Oral (Rat) LD50; 20000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]	
		Skin(human):104 mg/3d Intermit Mod	
		Skin(human):500 mg/7days mild	
		Skin: no adverse effect observed (not irritating) ^[1]	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute to specified data extracted from RTECS - Register of Toxic Effect of chemi	-	
CALCIUM SULFATE	Gypsum (calcium sulfate dihydrate) is a skin, eye, mucous membrane, and respiratory system irritant. Early studies of gypsum miners did not relate pneumoconiosis with chronic exposure to gypsum. Other studies in humans (as well as animals) showed no lung fibrosis produced by natural dusts of calcium sulfate except in the presence of silica. However, a series of studies reported chronic nonspecific respiratory diseases in gypsum industry workers in Gacki, Poland. Unlike other fibers, gypsum is very soluble in the body; its half-life in the lungs has been estimated as minutes. In four healthy men receiving calcium supplementation with calcium sulfate (CaSO4-1/2H2O) (200 or 220 mg) for 22 days, an average absorption of 28.3% was reported. Several feeding studies in pigs on the bioavailability of calcium in calcium supplements, including gypsum, have been conducted. The bioavailability of calcium in gypsum was similar to that for calcitic limestone, oyster shell flour, marble dust, and aragonite, ranging from 85 to 102%.		
UREA	Altered sleep time, change in motor activity, antipsychosis, dyspnea, methaemoglobinaemia, convulsions, lymphomas recorded. Carcinogenic by RTECS criteria. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the		

PastureSure	Impact	(NI)
-------------	--------	------

	spongy layer (spongiosis) and intracellular oedema of the For urea: There is little data that relates urea to human health oth The use of urea (at 10% concentration or less) in ointru- have indicated that the substance is nonallergenic and inappropriate secretion of antidiuretic hormone (SIADH) large amounts of urea. Most patients have tolerated ure possibility exists that infection of H. pylori in human stor Acute toxicity: The acute toxicity by urea is well deline NOTE: Substance has been shown to be mutagenic in cellular DNA.	er than its use in dermatology and so ents and creams to treat dry skin has virtually free from side effects. Among) should be noted, because its chronic as well, although diarrhoea is sometim mach may aggravate local effects by u eated by the oral route.	been widespread, and long term follow-up studies other clinical therapeutic uses, the treatment of form has involved long term oral administration of es reported after ingestion of 60-90 g/day. The irea because of ammonia generation.
CALCIUM PHOSPHATE, DIBASIC	for calcium: Toxicity from calcium is not common because the gastro intake of large amounts of calcium does not generally p However, more severe toxicity can occur when excess a amounts of vitamin D, which increases calcium absorpt calcium. Toxicity is manifested by abnormal deposition hypercalcaemia is often due to other causes, such as a	roduce any ill effects aside from cons calcium is ingested over long periods, ion. Calcium toxicity is also sometimes of calcium in tissues and by elevated t	tipation and an increased risk of kidney stones . or when calcium is combined with increased s found after excessive intravenous administration of olood calcium levels (hypercalcaemia). However,
PROPYLENE GLYCOL	The acute oral toxicity of propylene glycol is very low, a toxicity generally occurs only at plasma concentrations would be nearly impossible to reach toxic levels by consiglycol poisoning are usually related to either inappropria potential for long-term oral toxicity is also low. Because Administration as "generally recognized as safe" (GRAS Prolonged contact with propylene glycol is essentially n can produce slight transient conjunctivitis (the eye record The material may cause skin irritation after prolonged of dermatitis is often characterised by skin redness (eryther spongy layer (spongiosis) and intracellular oedema of the spongy layer (spongiosis) and spongiosis) and spongiosis and spongi	over 1 g/L, which requires extremely h suming foods or supplements, which c ate intravenous administration or accic of its low chronic oral toxicity, propyle S) for use as a direct food additive. on-irritating to the skin. Undiluted prop vers after the exposure is removed). r repeated exposure and may produce ema) and swelling the epidermis. Histo	high intake over a relatively short period of time. It contain at most 1 g/kg of PG. Cases of propylene lental ingestion of large quantities by children. The ne glycol was classified by the U. S. Food and Drug bylene glycol is minimally irritating to the eye, and e a contact dermatitis (nonallergic). This form of
CALCIUM SULFATE & UREA & CALCIUM PHOSPHATE, DIBASIC & CALCIUM PHOSPHATE, MONOBASIC	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases.		
Acute Toxicity	✓	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	¥	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×

Legend: X – Data either not available or does not fill the criteria for classification - Data available to make classification

x

Aspiration Hazard

Toxicity

×

Mutagenicity

	Endpoint	Test Duration (hr)	Species	Value	Source
PastureSure Impact (NI)	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	0.25h	Fish	75mg/l	4
calcium sulfate	EC50	72h	Algae or other aquatic plants	>79mg/l	2
	LC50	96h	Fish	>79mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	48h	Algae or other aquatic plants	7mg/l	4
urea	EC50	48h	Crustacea	6119-7061mg/l	4
	LC50	96h	Fish	4.65-8.48mg/l	4
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	>2.9mg/l	2
calcium phosphate, dibasic	EC50	72h	Algae or other aquatic plants	>4.4mg/l	2
	EC50	48h	Crustacea	>2.9mg/l	2
	LC50	96h	Fish	>13.5mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
calcium phosphate, monobasic	EC50(ECx)	48h	Crustacea	>100mg/l	Not Available
	EC50	72h	Algae or other aquatic plants	>100mg/l	Not Available

	EC50	48h	Crustacea	>100mg/l	Not Available
	LC50	96h	Fish	>100mg/l	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	336h	Algae or other aquatic plants	<5300mg/l	1
	EC50	72h	Algae or other aquatic plants	19300mg/l	2
propylene glycol	EC50	48h	Crustacea	>114.4mg/L	4
	LC50	96h	Fish	>10000mg/l	2
	EC50	96h	Algae or other aquatic plants	19000mg/l	2
Legend:	Ecotox databas		d Substances - Ecotoxicological Information - Aqua rd Assessment Data 6. NITE (Japan) - Bioconcenti		

DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
calcium sulfate	HIGH	HIGH
urea	LOW	LOW
propylene glycol	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation	
calcium sulfate	LOW (LogKOW = -2.2002)	
urea	LOW (BCF = 10)	
propylene glycol	LOW (BCF = 1)	

Mobility in soil

Ingredient	Mobility
calcium sulfate	LOW (KOC = 6.124)
urea	LOW (KOC = 4.191)
propylene glycol	HIGH (KOC = 1)

SECTION 13 Disposal considerations

Waste treatment methods Product / Packaging disposal It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

SECTION 14 Transport information

Labels Required	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
calcium sulfate	Not Available
urea	Not Available
calcium phosphate, dibasic	Not Available
calcium phosphate, monobasic	Not Available
propylene glycol	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
calcium sulfate	Not Available
urea	Not Available
calcium phosphate, dibasic	Not Available
calcium phosphate, monobasic	Not Available
propylene glycol	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002571	Fertilisers Subsidiary Hazard Group Standard 2020	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

calcium sulfate is found on the following regulatory lists		
New Zealand Inventory of Chemicals (NZIoC)	New Zealand Workplace Exposure Standards (WES)	
urea is found on the following regulatory lists		
New Zealand Approved Hazardous Substances with controls	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	of Chemicals - Classification Data	
of Chemicals	New Zealand Inventory of Chemicals (NZIoC)	
calcium phosphate, dibasic is found on the following regulatory lists		
New Zealand Approved Hazardous Substances with controls	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	of Chemicals - Classification Data	
of Chemicals	New Zealand Inventory of Chemicals (NZIoC)	
calcium phosphate, monobasic is found on the following regulatory lists		
New Zealand Approved Hazardous Substances with controls	New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification	of Chemicals - Classification Data	
of Chemicals	New Zealand Inventory of Chemicals (NZIoC)	
propylene glycol is found on the following regulatory lists		
New Zealand Inventory of Chemicals (NZIoC)	New Zealand Workplace Exposure Standards (WES)	
Hazardous Substance Location		

dous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia	Yes

National Inventory	Status	
Non-Industrial Use		
Canada - DSL	Yes	
Canada - NDSL	No (calcium sulfate; urea; calcium phosphate, dibasic; calcium phosphate, monobasic; propylene glycol)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	15/09/2022
Initial Date	24/10/2019

SDS Version Summarv

Version	Date of Update	Sections Updated
3.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value I OD. Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.